

C	Zone	V /	C -	
I-racc	/nna	varn/		ınr
urass	LUITE	Talli/	CU	IUI

**Grass Zone Denier** 

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile Weight

Backing

**Tuft Gauge** 

**Total Weight** 

**Tuft Bind** 

Permeability

Features

**Test Data** 

## PE / Field Green / Apple / Tan

9,900/9

PE / Field Green / Beige

5,040 / 12

Omega / Rhombus

1 7/8"

90 oz.

15 / 18 PP 2-Part / 20oz. EnviroLoc™

1/2"

116 oz.

> 8 lbs.

> 300 inches per / SY

EnviroLoc™, HeatBlock™, Deluster, UV Stabilizers

ASTM Certified F1292, F1951

## SYNBlue 949

A knockout combination of multi-colored grass blades incorporating field green, apple, olive, and beige in the surface color makes this variety of turf the undisputed champion of realism in artificial grass.



Unmatched Lifetime Warranty



EnviroLoc™ Plant-Based Backing



Deluster and UV Protection





## RECOMMENDED USES





















Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Omega / Rhombus		
Standard Color	Field / Olive / Apple / Tan		
Fabric Construction	Tufted		
Second Yarn Polymer Thatch	Polyethylene		
Secondary Yarn Color	Field Green / Beige		

Primary Backing	15/18 PP 2-Part	
Coating Type	20 oz. EnviroLoc™	
PE Yarn Denier / Ends	9,900 / 9	
Texturized Thatch Denier / Ends	5,040 / 12	
Warranty Period	Limited Lifetime	

Finish Fabric	English System		ASTM Test	
Nominal Specification	Value	Units	Method	
Pile Height (Nominal)	1 7/8	inches	D-5823	
Face Weight	90	oz/yd²	D-5848	
Total Fabric Weight	116	oz/yd²	D-5848	
Primary Backing Weight	6	oz/yd²	D-5848	
Secondary Coating Weight	20	oz/yd²	D-5848	
Tuft Bind	> 8	lbs.	D-1335	
Grab Tear Strength (Average)	> 200	lbs.	D-5034	
Total Yarn Linear Density	14,940	Denier	D-1577	
Elongation to Break	> 30	%	D-2256	
Yarn Breaking Strength	> 20	lbs.	D-5793	
Machine Guage	1/2	inches	D-5793	
Flammability	Passed	-	D-2859	
Water Permeability	344.31	in/hr	D-1551	
Fabric Width	15	ft	-	







