



TEE STRIKE

This artificial tee-line grass is so dense it easily supports a standard golf tee for a natural, true-to-life feel allowing golfers to swing on a surface that won't grab the club-head. The durable nylon construction offers unmatched performance over PE with a quick ROI for golf facilities.

SKU	SS301
Grass Zone Yarn/Color	Nylon / Verde
Grass Zone Denier	7,000 / 8
Thatch Zone Yarn/Color	-
Thatch Zone Denier	-
Grass Zone Yarn Shape	Textured Diamond
Finished Pile Height	1"
Finished Pile Weight	120 oz.
Backing	15 / 18 PP 2-Part / 22oz. EnviroLoc™
Tuft Gauge	3/16"
Total Weight	148 oz.
Tuft Bind	> 8 lbs.
Permeability	-
Features	EnviroLoc™ UV Stabilizers
Test Data	ASTM Certified F1292, F1951



10 Year Warranty



EnviroLoc™ Plant-Based Backing



UV Protection



Not to scale. For illustration only.

ASK FOR A...



Dave Pelz
SHOTSTOPPER™
Installation System



GreensMaster™
CERTIFIED
Installer



RECOMMENDED USES



GOLF

Primary Yarn Polymer	Nylon	Primary Backing	15/18 PP 2-Part
Yarn Cross Section	Textured Diamond	Coating Type	22 oz. EnviroLoc™
Standard Color	Verde	PE Yarn Denier / Ends	7,000 / 8
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	-
Second Yarn Polymer Thatch	-	Warranty Period	10 years
Secondary Yarn Color	-		

Finish Fabric	English System		ASTM Test
	Nominal Specification	Value	Units
Pile Height (Nominal)	1	inches	D-5823
Face Weight	120	oz/yd ²	D-5848
Total Fabric Weight	148	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	22	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	7,000	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/16	inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	-	in/hr	D-1551
Fabric Width	6 & 12	ft	-