

| SKU                    | SF343   |  |
|------------------------|---|--|
| Grass Zone Yarn/Color  | PE / Field Green / Apple  |  |
| Grass Zone Denier      | 10,800 / 6  |  |
| Thatch Zone Yarn/Color | PE / Field Green / Beige  |  |
| Thatch Zone Denier     | 5,000 / 8   |  |
| Grass Zone Yarn Shape  | Omega   |  |
| Finished Pile Height   | 2"  |  |
| Finished Pile Weight   | 80 oz.  |  |
| Backing                | 15 / 18 PP 2-Part / 22oz. EnviroLoc+™   |  |
| Tuft Gauge             | 3/8"  |  |
| Total Weight           | 108 oz.   |  |
| Tuft Bind              | > 8 lbs.  |  |
| Permeability           | > 1,000 inches per / SY   |  |
| Features               | Sanitized®, EnviroLoc+™, StatBlock™<br>Anti-Static, DualChill™ IR Reflective,<br>Deluster, UV Stabilizers |  |
| Test Data              | ASTM E108 Class A Fire Rating,  |  |

## **SYN**Fescue 343

Offering superior dimensional strength and stability while remaining easy on the eyes and wallet. Incorporating Super Yarn™ technology, this landscape grass offers extreme flexibility and durability, creating the perfect solution for multiple applications.

Unmatched Lifetime Warranty

nviroLoc+™ Plant-Based Backing

Deluster + UV Protection

ASTM E108 Class A Fire Rating

## SUPER YARN<sup>™</sup> TECHNOLOGY

Sanitized® DualChill™ Antimicrobial IR Reflective

**DualChill**<sup>™</sup> **StatBlock**<sup>™</sup> R Reflective Anti-Static



RECOMMENDED USES

**(%)** 

















F1292, F1551, F1951, IPEMA

Certified



| Primary Yarn Polymer       | Polyethylene        |
|----------------------------|---------------------|
| Yarn Cross Section         | Omega               |
| Standard Color             | Field Green / Apple |
| Fabric Construction        | Tufted              |
| Second Yarn Polymer Thatch | Polyethylene        |
| Secondary Yarn Color       | Field Green / Beige |

| Primary Backing                 | 15/18 PP 2-Part   |  |  |
|---------------------------------|-------------------|--|--|
| Coating Type                    | 22 oz. EnviroLoc+ |  |  |
| PE Yarn Denier / Ends           | 10,800 / 6        |  |  |
| Texturized Thatch Denier / Ends | 5,000 / 8         |  |  |
| Warranty Period                 | Limited Lifetime  |  |  |

| Finish Fabric                | English | English System |        |
|------------------------------|---------|----------------|--------|
| Nominal Specification        | Value   | Units          | Method |
| Pile Height (Nominal)        | 2       | inches         | D-5823 |
| Face Weight                  | 80      | oz/yd²         | D-5848 |
| Total Fabric Weight          | 108     | oz/yd²         | D-5848 |
| Primary Backing Weight       | 6       | oz/yd²         | D-5848 |
| Secondary Coating Weight     | 22      | oz/yd²         | D-5848 |
| Tuft Bind                    | > 8     | lbs.           | D-1335 |
| Grab Tear Strength (Average) | > 200   | lbs.           | D-5034 |
| Total Yarn Linear Density    | 15,800  | Denier         | D-1577 |
| Elongation to Break          | > 30    | %              | D-2256 |
| Yarn Breaking Strength       | > 20    | lbs.           | D-5793 |
| Machine Gauge                | 3/8     | inches         | D-5793 |
| Flammability                 | Passed  | -              | D-2859 |
| Water Permeability           | > 1,000 | in/hr          | D-1551 |
| Fabric Width                 | 15      | ft             | -      |
|                              |         |                |        |







