



## PET PREMIUM

Excellent durability, max drainage, anti-static, and Sanitized® technology make this artificial grass ideal for pet play and agility, including animals of all sizes. Easy to clean and beautiful year-round, make this the perfect pet grass for residential and commercial applications.

SKU	SAX47 PETS
Grass Zone Yarn/Color	PE / Field Green / Olive / Apple
Grass Zone Denier	9,900 / 9
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	Soft Omega
Finished Pile Height	1 5/8"
Finished Pile Weight	100 oz.
Backing	15 / 18 PP 2-Part / 22oz. EnviroLoc+™
Tuft Gauge	3/8"
Total Weight	128 oz.
Tuft Bind	> 8 lbs.
Permeability	> 1,400 inches per / SY
Features	Sanitized®, EnviroLoc+™, StatBlock™ Anti-Static, DualChill™ IR Reflective, Deluster, UV Stabilizers
Test Data	ASTM E108 Class A Fire Rating, F1292, F1951, IPEMA Certified

- Unmatched Lifetime Warranty
- EnviroLoc+™ Plant-Based Backing
- Deluster + UV Protection
- ASTM E108 Class A Fire Rating

### SUPER YARN™ TECHNOLOGY

**Sanitized®**  
Antimicrobial

**DualChill™**  
IR Reflective

**StatBlock™**  
Anti-Static



Not to scale. For illustration only. Installation method may vary by region.

### RECOMMENDED USES



PETS



LANDSCAPE



PLAY



ROOFTOP



<b>Primary Yarn Polymer</b>	Polyethylene	<b>Primary Backing</b>	15/18 PP 2-Part
<b>Yarn Cross Section</b>	Soft Omega	<b>Coating Type</b>	22 oz. EnviroLoc+
<b>Standard Color</b>	Field Green / Olive / Apple	<b>PE Yarn Denier / Ends</b>	9,900 / 9
<b>Fabric Construction</b>	Tufted	<b>Texturized Thatch Denier / Ends</b>	5,000 / 8
<b>Second Yarn Polymer Thatch</b>	Polyethylene	<b>Warranty Period</b>	Limited Lifetime
<b>Secondary Yarn Color</b>	Field Green / Beige		

Finish Fabric	English System		ASTM Test
	<i>Nominal Specification</i>	<i>Value</i>	<i>Units</i>
<b>Pile Height (Nominal)</b>	1 5/8	inches	D-5823
<b>Face Weight</b>	100	oz/yd <sup>2</sup>	D-5848
<b>Total Fabric Weight</b>	128	oz/yd <sup>2</sup>	D-5848
<b>Primary Backing Weight</b>	6	oz/yd <sup>2</sup>	D-5848
<b>Secondary Coating Weight</b>	22	oz/yd <sup>2</sup>	D-5848
<b>Tuft Bind</b>	> 8	lbs.	D-1335
<b>Grab Tear Strength (Average)</b>	> 200	lbs.	D-5034
<b>Total Yarn Linear Density</b>	14,900	Denier	D-1577
<b>Elongation to Break</b>	> 30	%	D-2256
<b>Yarn Breaking Strength</b>	> 20	lbs.	D-5793
<b>Machine Gauge</b>	3/8	inches	D-5793
<b>Flammability</b>	Passed	-	D-2859
<b>Water Permeability</b>	> 1,400	in/hr	D-1551
<b>Fabric Width</b>	15	ft	-